



e-ISSN: 2278-8875

p-ISSN: 2320-3765

# International Journal of Advanced Research

**in Electrical, Electronics and Instrumentation Engineering**

**Volume 15, Issue 3, March 2026**

**ISSN** INTERNATIONAL  
STANDARD  
SERIAL  
NUMBER  
INDIA

**Impact Factor: 8.807**

☎ 9940 572 462

☎ 6381 907 438

✉ [ijareeie@gmail.com](mailto:ijareeie@gmail.com)

@ [www.ijareeie.com](http://www.ijareeie.com)



# Smart Transformer Theft Protection and Maintenance Monitoring System

Nida Tabrejkhani<sup>1</sup>, Bushra Irfan Shaikh<sup>1</sup>, Abubakhar Siddique Alauddin Mujawar<sup>1</sup>,  
Mrs. Priyanka P. Thorat<sup>2</sup>

Department of Electrical Engineering, Dr. Bapuji Salunkhe Institute of Engineering and Technology, Kolhapur,  
Maharashtra, India<sup>1</sup>

Lecturer, Department of Electrical Engineering, Dr. Bapuji Salunkhe Institute of Engineering and Technology,  
Kolhapur, Maharashtra, India<sup>2</sup>

**ABSTRACT:** Power distribution transformers are critical components of electrical networks but are increasingly vulnerable to theft, vandalism, and undetected operational faults, particularly in remote and outdoor installations. Theft of copper windings and insulating oil results in financial losses, prolonged outages, and safety risks, while conventional time-based maintenance often fails to identify early signs of overheating, overloading, or oil leakage. This paper presents a GSM-based Smart Transformer Theft Protection and Maintenance Monitoring System that integrates asset security with real-time condition monitoring. The system employs sensors to monitor key parameters such as temperature, oil level, load conditions, vibration, and unauthorized access. An Arduino-based microcontroller processes sensor data and compares it with predefined thresholds to detect abnormal conditions or theft attempts. Upon detection, a GSM module transmits immediate SMS alerts to authorized personnel, while an optional GPS module enables location tracking. The proposed low-cost and reliable solution enhances transformer security, supports predictive maintenance, reduces downtime, and improves the overall reliability and resilience of power distribution networks.

**KEYWORDS:** Smart Transformer Monitoring; Transformer Theft Protection; Condition-Based Maintenance; GSM Communication; Internet of Things (IoT); Asset Security; Predictive Maintenance; Distribution Transformer Monitoring; Remote Fault Detection; Power Distribution Network.

## I. INTRODUCTION

Power distribution transformers are critical assets in electrical networks, yet they are increasingly vulnerable to theft, vandalism, and undetected operational faults. Transformer theft particularly of oil, copper windings, and auxiliary component results in significant financial losses, prolonged power outages, and safety risks to both utilities and the public. At the same time, the lack of continuous condition monitoring often leads to delayed maintenance, unexpected failures, and reduced transformer lifespan. The Transformer Theft Protection and Maintenance Monitoring System is developed to address these challenges through an integrated approach that combines asset security with real-time condition monitoring. The system employs anti-theft measures such as access intrusion detection, tamper alerts, and location tracking, alongside maintenance monitoring features including temperature, load, oil level, and fault detection sensors. These components work together to provide early warnings, enable predictive maintenance, and ensure rapid response to unauthorized activities. By leveraging modern sensing, communication, and data analytics technologies, the system enhances transformer reliability, reduces operational losses, and improves maintenance efficiency. This integrated solution supports power utilities in safeguarding infrastructure, minimizing downtime, and transitioning from reactive to proactive asset management, thereby strengthening the overall resilience of the power distribution network.

Power transformers are high-value assets essential for reliable electricity distribution. In many regions, transformers are frequently targeted for theft due to the resale value of copper windings and insulating oil. Theft and vandalism not only cause financial losses but also lead to prolonged outages, equipment damage, and public safety risks.

In parallel, traditional transformer maintenance relies on periodic manual inspections, which may fail to detect early signs of overheating, overloading, insulation degradation, or oil leakage. This reactive approach increases the likelihood of sudden failures and shortens transformer lifespan. An integrated Transformer Theft Protection and Maintenance Monitoring System is therefore essential to ensure asset security, operational reliability, and cost-effective maintenance. Distribution transformers are critical components of electrical power distribution systems, serving as the final stage in voltage transformation before electricity is supplied to end users. These transformers are widely deployed



in outdoor environments such as roadside installations, agricultural fields, and rural areas, where they are often subjected to harsh weather conditions and limited physical security. Due to their exposed locations, distribution transformers are highly susceptible to theft, vandalism, and operational failures, which pose significant challenges to power utilities.

Transformer theft has emerged as a serious concern in many regions, particularly in remote and less monitored areas. Components such as copper windings and transformer oil have high commercial value and are frequently targeted, resulting in substantial financial losses and prolonged power outages.

Conventional security mechanisms, including physical barriers and routine manual inspections, are largely reactive in nature and fail to provide timely detection or prevention of theft attempts. In most cases, theft or tampering is identified only after a complete transformer failure has occurred. In addition to security issues, inadequate maintenance and the absence of continuous condition monitoring adversely affect transformer performance and service life. Key operational parameters such as temperature, oil level, load conditions, and vibration must remain within permissible limits to ensure reliable operation.

facilitates prompt corrective action and reduces the risk of severe damage or prolonged outages. The use of GSM technology offers several advantages, including wide network coverage, reliability, low cost, and independence from internet connectivity. These features make the system particularly suitable for deployment in rural and remote areas where internet-based monitoring solutions may not be feasible. Furthermore, the system supports a shift from conventional reactive maintenance to a more efficient predictive and preventive maintenance approach. The implementation of a GSM-based smart monitoring and theft protection system enhances the reliability, safety, and efficiency of power distribution networks. It contributes to improved asset management, reduced operational costs, and extended transformer lifespan. By providing real-time monitoring and early fault detection, the system minimizes downtime and ensures uninterrupted power supply to consumers. In conclusion, the GSM-based Smart Transformer Theft Protection and Maintenance Monitoring System presents a practical and effective solution to the challenges associated with transformer security and maintenance. The integration of sensor-based monitoring with GSM communication enables continuous supervision, rapid fault detection, Traditional maintenance practices are typically schedule-based and do not account for real-time operating conditions, leading to delayed fault identification and unexpected breakdowns. Recent advancements in embedded systems and wireless communication technologies have enabled the development of intelligent monitoring solutions for power system assets. A GSM-based Smart Transformer Theft Protection and Maintenance Monitoring System integrates sensors, a microcontroller, and a GSM communication module to provide continuous monitoring and remote alerting. The GSM module enables wireless communication over cellular networks, allowing the system to transmit real-time notifications to utility personnel through Short Message Service (SMS). In the proposed system, various sensors are employed to monitor critical transformer parameters such as temperature rise, oil level variation, abnormal vibration, and unauthorized physical access. The microcontroller continuously processes sensor data and compares it with predefined threshold values. Upon detection of abnormal conditions or theft attempts, the system activates the GSM module to send immediate alert messages to concerned authorities. This and timely alert generation, making it a valuable contribution toward the modernization of electrical power distribution systems.

## II. KEY FUNCTIONS OF THE SYSTEM

### 1. Theft Protection

Intrusion Detection: Sensors detect unauthorized opening of transformer doors or panels.

Tamper Detection: Vibration, tilt, or motion sensors detect attempts to move or dismantle the transformer.

Theft of Consumables: Abrupt drops in oil level trigger alarms, indicating illegal extraction.

Location Awareness: GPS tracking (optional) can locate a transformer if moved.

### 2. Maintenance Monitoring

Temperature Tracking: Measures transformer winding and oil temperature to identify overheating.

Voltage & Current Monitoring: Detects overloads, imbalances, or abnormal electrical conditions.

Oil Level and Quality: Sensors measure oil level, and advanced systems may assess oil quality (e.g., dissolved gas analysis).

Fault Detection: Identifies anomalies like short circuits or insulation faults before they cause failures.

### 3. Communication & Alerts

Data and alerts are sent in real time using communication technologies such as:

GSM/LTE (SMS or mobile data),



Wi-Fi, NB-IoT,  
Wired Ethernet support where available.

#### 4. Data Management & Visualization

A central platform (cloud dashboard or utility SCADA) shows live status, historical trends, and alarms. Operators can monitor multiple transformers from a single interface.

### III. LITERATURE REVIEW

#### Integrated Transformer Theft Protection & Monitoring Systems

Smart Transformer Theft Protection and Maintenance Monitoring System A recent (2025) study proposes an IoT-based system combining theft detection and maintenance monitoring. It uses sensors for temperature, oil level, vibration (for tampering), voltage/current, and communicates data via GSM/Thing Speak for remote monitoring. Theft or abnormal events trigger alerts.

#### IoT-based Power Theft and Transformer Monitoring

Student project reports highlight systems that detect power theft, temperature variations, and oil level changes using microcontrollers and IoT sensors — demonstrating practical prototypes to safeguard assets and reduce revenue loss. Transformer Condition & Maintenance Monitoring

#### IoT-based Condition Monitoring of Transformer

A 2022 paper presents an IoT system to monitor transformer oil temperature and gas levels (using DGA concepts) to detect faults and avoid failures, aiming for early fault detection and remote monitoring.

#### Condition Monitoring of Power Transformers — Practical Approach

Discusses transformer health indices and failure probability to support asset management and predictive maintenance strategies, moving beyond time-based maintenance.

#### Transformer Health Monitoring System (THMS) Review

A 2023 review outlines real-time sensor-based monitoring of voltage, current, temperature, and oil level to assess transformer condition and detect faults early.

#### Review of Transformer Health Monitoring Technologies

Surveys technologies used in transformer health monitoring systems and discusses real-time data collection and predictive maintenance to improve reliability and reduce downtime.

#### Transformer Health Monitoring and Protection Using IoT

Highlights sensor network implementations with IoT connectivity (e.g., ESP8266) to monitor transformer parameters remotely, improving accuracy and maintenance efficiency.

### IV. OBJECTIVES

- To develop an effective theft protection mechanism capable of detecting unauthorized access, tampering, oil theft, and transformer displacement.
- To implement continuous maintenance monitoring by tracking critical parameters such as temperature, oil level, voltage, and current.
- To enable real-time monitoring and wireless communication using GSM technology for remote supervision.
- To design a data analysis and alert system that compares sensor readings with predefined thresholds and generates instant notifications during abnormal conditions.
- To ensure system reliability and scalability, allowing deployment across multiple transformers in diverse environments.
- To implement a real-time alert and notification mechanism for rapid response to faults or theft attempts.
- To provide remote asset visibility, enabling utilities to monitor transformer status from a centralized location.
- To support integration with existing utility infrastructure, including SCADA or IoT-based platforms.
- To enable data logging and reporting for trend analysis, preventive maintenance planning, and performance evaluation.
- To enhance operational and public safety by detecting hazardous conditions at an early stage.

## V. CIRCUIT DIAGRAM




Fig 1. Block Diagram of the Smart Transformer Theft Protection and Maintenance Monitoring System

The proposed Smart Transformer Theft Protection and Maintenance Monitoring System is designed to enhance the safety, reliability, and maintenance efficiency of distribution transformers by integrating sensing, processing, power management, and wireless communication units, as shown in the above block diagram. The system is powered by a single-phase 230 V AC source, which is stepped down using a transformer and managed through a charge controller. Li-Po battery sets provide backup power, ensuring uninterrupted operation during power failures. An Automatic Transfer Switch (ATS) intelligently selects between the main supply and battery backup. The LM7805 voltage regulator supplies a stable 5 V DC required for the Arduino Uno R3 and connected sensors. At the core of the system is the Arduino Uno R3, which acts as the processing unit. It continuously collects and processes data from multiple sensors installed on the transformer. An IR sensor and Hall Effect sensor are used for theft detection by monitoring unauthorized movement, tampering, or abnormal current conditions. The weight sensor and load cell help detect transformer removal or partial theft by identifying sudden changes in weight. A GPS module provides real-time location tracking of the transformer, which is especially useful in theft scenarios. For maintenance monitoring, an oil level sensor checks transformer oil status, while a temperature sensor monitors overheating conditions that could lead to faults or failures. These parameters help in predictive maintenance and early fault detection, reducing downtime and repair costs. The GSM module serves as the communication unit, sending real-time alerts and status updates to authorized personnel via wireless SMS. In the event of theft, overheating, oil leakage, or overload, immediate notifications are sent, enabling quick response and corrective action. Overall, this smart system improves transformer security, supports condition-based maintenance, reduces power losses, and enhances the reliability of power distribution networks through automation and real-time monitoring.

## VI. CONCLUSION


The Smart Transformer Theft Protection and Maintenance Monitoring System presented in this work offers a comprehensive approach to improving the security and operational performance of distribution transformers. By integrating theft detection mechanisms with real-time condition monitoring, the system addresses two major challenges faced by power utilities asset protection and preventive maintenance. The use of multiple sensors enables continuous tracking of critical parameters such as temperature, oil level, load conditions, and physical tampering, ensuring early identification of abnormal situations. The incorporation of GSM based communication allows instant transmission of alerts to authorized personnel, enabling timely intervention and reducing the risk of prolonged outages or severe equipment damage. The inclusion of backup power support further enhances system reliability during power interruptions. Overall, the proposed system supports a transition from reactive maintenance practices to a more proactive and predictive approach. It improves transformer lifespan, enhances public and operational safety, minimizes



financial losses, and strengthens the resilience of power distribution networks. The low-cost and scalable architecture makes it suitable for practical deployment, particularly in remote and infrastructure-limited areas.

#### REFERENCES

- [1] B. L. Theraja and A. K. Theraja, A Textbook of Electrical Technology, vol. II, S. Chand & Company Ltd., New Delhi, 2017.
- [2] M. Kolap, S. K. Patel, P. V. Gaikwad, and S. S. Chougule, “Design and Implementation of Real Time Transformer Monitoring System Using IoT Technology,” International Journal of Innovative Research in Electrical, Electronics, Instrumentation and Control Engineering (IJIREEICE), 2022. DOI: 10.17148/IJIREEICE.2022.10560.
- [3] V. H. Shinde, S. R. Rasal and S. S. Shirsat, “IoT Based Condition Monitoring System for Distribution Transformer,” International Journal of Trend in Scientific Research and Development (IJTSRD), vol. 3, no. 4, pp. 1840–1844, Jul.–Aug. 2019.
- [4] <https://www.ijtsrd.com/paper/37500/iot-based-condition-monitoring-system-for-distribution-transformer/vishal-h-shinde>
- [5] <https://www.ijritcc.org/download/secure?type=paper&paperid=IJRITCC0525>
- [6] S. K. S. Krishna, G. Bharadwaj, K. V. G. and M. D. Monika, “Smart Grid Enabled Transformer Monitoring System Using IoT,” International Journal of Electrical and Electronics Engineering (IJEEE), vol. 8, no. 3, pp. 15–22, 2021.



INNO  SPACE  
SJIF Scientific Journal Impact Factor

 **doi**<sup>®</sup>  
**cross** **ref**

**ISSN** INTERNATIONAL  
STANDARD  
SERIAL  
NUMBER  
INDIA



# International Journal of Advanced Research

in Electrical, Electronics and Instrumentation Engineering

 9940 572 462  6381 907 438  [ijareeie@gmail.com](mailto:ijareeie@gmail.com)



[www.ijareeie.com](http://www.ijareeie.com)

Scan to save the contact details